

PRISM JOHNSON LIMITED

(Formerly Prism Cement Limited)

RMC India Division

Construction Chemicals Business

Technical Datasheet

Construction Chemicals

ENDURAMOL SR 2204

DESCRIPTION

ENDURAMOL SR 2204 is high grade super plasticizer based on polycarboxylate ether polymer with long lateral chain. It doesn't have any water reduction but having very good slump retention property in concrete application. It is worked as a delayed dispersant type super plasticizer in concrete. It produces concrete with exceptionally workable characteristics referred to as high flow able concrete with combination of **ENDURAMOL** grade water reducer. It helps in producing concrete of high workability and high strength.

WORKING PRINCIPLES

It increases the workability, in combination of **ENDURAMOL** type water reduce, of concrete mixes by its powerful electro-static force and steric hindrance on cement particles, which in turn helps to produce high workable concrete or enables in significant reduction in free water content.

PRODUCT APPLICATION

- ✓ Concrete Admixtures
- ✓ Ready-mix concrete
- ✓ High performance concrete for durability
- ✓ High early and ultimate strength concrete
- ✓ High workability without segregation or bleeding
- ✓ Precast & Pre-stressed concrete
- ✓ Concrete containing pozzolans such as micro silica, GGBFS, PFA.

ADVANTAGES

- ✓ Excellent slump retention property
- ✓ Improve workability
- ✓ Elimination of vibration and reduced labour cost in placing
- ✓ Significant increase in early & ultimate strengths
- ✓ Higher E modulus
- ✓ Improved adhesion to reinforcing and stressing steel
- ✓ Better resistance to carbonation and other aggressive atmospheric conditions
- ✓ Lower permeability - increased durability
- ✓ Reduced shrinkage and creep
- ✓ It can be easily mixed with **ENDURAMOL** Grade WATER REDUCING TYPE and HYBRID TYPE molecule to get enhanced performance.

PROPERTIES

| | |
|---------------------------|------------------------------------|
| Appearance | : Colorless to faint yellow Liquid |
| pH | : 6.0 ± 1 |
| Specific Gravity at 30 °C | : 1.100 ± 0.05 |
| Chloride content | : Nil to 0.03% Max |
| Solid content (% by mass) | : 51±1 |

RECOMMENDED DOSAGE

Typically, 0.3 to 1.2% by weight of cement / cementitious is recommended. Can be used in individual or blend with water reducer type polymer. However optimum dosage of **ENDURAMOL SR 2204** should be determined with trial mixes. Because of variations in concrete materials, job site conditions, and/or applications, dosages outside of the recommended range may be required. In such cases, contact your local PRISM JOHNSON, RMC INDIA - CCB representative for additional information on **ENDURAMOL SR 2204** molecule or on its use in developing concrete mixes with special effects of over dosage. A severe over-dosage of **ENDURAMOL SR 2204** can result in the following:

- ❖ Extension of initial and final set
- ❖ Bleed / segregation of mix
- ❖ Increased plastic shrinkage

CAUTION

ENDURAMOL SR 2204 should be dispensed through suitable calibrated dosing equipment. It should not be premixed with other chemicals if not recommended. It should be mixed thoroughly before use. Do not add **ENDURAMOL SR 2204** to dry cement.

SAFETY PRECAUTION

ENDURAMOL SR 2204 is an acidic solution. It may cause irritation to eye and skin on direct or prolonged contact. Suitable protective gloves and goggles should be worn. Splash on skin should be cleaned with water. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. For further information on safe handling, storage and disposal, you are advised to follow MSDS.

PACKAGING & DELIVERY

Delivered in 230 kg HDPE barrels or & bulk tanker as per requirements and mutual understanding

STORAGE

Keep in cool and dry place under shade and away from direct sunlight

SHELF LIFE

12 months from the manufacturing in original unopened condition.

FURTHER INFORMATION

PRISM JOHNSON LIMITED

RMC (INDIA) Division

Construction Chemicals Business

Address: Village-Gadab Khar Devli, Mumbai – Goa Road,
Taluka - Pen, District - Raigad, Maharashtra – 402 107.

Phone: +91-2143-274476 /101/102/103/104

Fax :+91-2143-274100/476

Email: ccb@rmcindia.com

www.rmcindia.com